

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 050 328 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
18.12.2002 Bulletin 2002/51

(51) Int Cl.7: **A63F 13/12, H04N 7/173**

(21) Application number: **00303282.8**

(22) Date of filing: **18.04.2000**

(54) Interactive applications

Interaktive Anwendungen

Applications interactives

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**

(30) Priority: **04.05.1999 EP 99303495**

(43) Date of publication of application:
08.11.2000 Bulletin 2000/45

(73) Proprietor: **Two Way TV Limited**
Avonmore Road, London W14 8TS (GB)

(72) Inventors:
• **Malaure, Jason Robert**
Twickenham, Middlesex TW2 5RN (GB)

• **Kydd, Richard Andrew**
Twickenham, Middlesex TW2 5TT (GB)

(74) Representative: **Skone James, Robert Edmund**
GILL JENNINGS & EVERY
Broadgate House
7 Eldon Street
London EC2M 7LH (GB)

(56) References cited:
WO-A-95/15653 **US-A- 5 537 143**
US-A- 5 850 447

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 1 050 328 B1

Description

[0001] The present invention relates to a method and apparatus for broadcasting interactive applications to a plurality of users via respective user interfaces.

[0002] In conventional interactive broadcast systems, data is broadcast to a plurality of user interfaces (e.g. televisions with set-top boxes) from a central control, e.g. computer, system (CCS). In order to deliver timed applications it is necessary to provide a local clock generator with each user interface. The user interface can then deliver the interactive application with reference to the signal from the local clock generator. The local clock generator is then synchronised with a central clock at the CCS to ensure that the interactive application is performed simultaneously at all user interfaces. However, since this means that the local clock must be adjustable, it is possible for the clock adjustment to be used in a fraudulent way. For instance a user can receive a quiz game on two user interfaces, one where he has deliberately adjusted the local clock and the other not. The user can then view the answers on the one user interface and enter the correct answers on the other user interface before it becomes locked out.

[0003] Previous proposals for detecting fraud are described in US-A-5850447 and WO-A-95/15653. In these cases, the local user interfaces detect fraud and notify the CCS. This itself can be compromised locally in some cases.

[0004] In accordance with one aspect of the present invention there is provided an interactive broadcast system comprising a plurality of user interfaces each comprising a local clock signal generator, wherein each user interface delivers interactive applications to a respective user with reference to its respective local clock signal; and a central control system (CCS) for broadcasting data to the user interfaces and for receiving data sent at a specific local time from the user interfaces, the CCS being adapted to identify fraudulent users by comparing the time at which said data are returned from a plurality of the user interfaces.

[0005] In accordance with a second aspect of the present invention there is provided a method of detecting fraudulent users in an interactive broadcast system, the method comprising

- (1) broadcasting data to a plurality of user interfaces from a central control system (CCS) ;
- (2) generating a local clock signal at each user interface;
- (3) delivering an interactive application to a respective user from each user interface with reference to its respective local clock signal;
- (4) receiving at the CCS data sent from the local interfaces at a specific local time; and,
- (5) identifying fraudulent users by comparing the time at which said data are returned from a plurality of the local interfaces.

[0006] In contrast to the previous proposals, the CCS detects fraudulent use by comparing the time of receipt of data from a plurality of user interfaces. It is thus not dependent on data received from a single interface.

[0007] In one method, step (4) comprises first sending a return path request to the user interfaces, step (5) comprising monitoring the time of receipt of return path data generated by the user interfaces in response to the return path request to identify user interfaces which have sent return path data which is advanced or delayed by more than a predetermined threshold. For example, the return path request may cause the user interfaces to return a local score at the end of an interactive application as determined by the user interface.

[0008] In another method, the local interfaces could be automatically controlled to return certain data, e.g. a score, at the end of an interactive game or at some other predetermined game time and not directly in response to a request from the CCS. However, the CCS will know when this return data is expected and can make the necessary comparisons.

[0009] The user interfaces may utilise their respective local clock signals in a number of ways. In a first example an application start signal is broadcast to the user interfaces by the CCS. The user interfaces calculate an application time local clock signal with reference to the application start signal. Each user interface can then deliver the interactive application with reference to its respective application time local clock signal. In a second example a central clock signal is periodically broadcast to the user interfaces representing a central time. The user interfaces can then calculate an offset signal with reference to the central clock signal and a respective local clock signal. The offset signal can then be used by the user interfaces at any time to determine the central time from their local clock signal. This can conveniently be implemented as part of a repetitive broadcast as described in EP-A-0998145.

[0010] The interactive application may take a variety of different forms - for instance it may comprise a video game which is played simultaneously by a number of remote users, or a quiz game played simultaneously by a number of remote users. The application may be broadcast in conjunction with a live TV event. For instance the application may enable the user to take part in a live TV quiz, or predict the occurrence of certain events in a live sporting event.

[0011] An example of the present invention will now be described with reference to the accompanying drawings, in which:

Figure 1 is a schematic diagram of a digital broadcast network; and,

Figure 2 is a schematic diagram of a user interface.

[0012] The digital broadcast network shown in Figure 1 comprises an interactive game control system 1 including a central control, in this case computer, system 2, an application data store 3 and a CCS clock 40. The application data store 3 contains setup data and real time data which can be accessed and amended by the CCS 2. The setup data may comprise executable program files, bitmaps, sound samples, video clips, and other multimedia and data resources. The real time data comprises data which is broadcast after the scheduled start time (eg question/answer data for a quiz game application). The setup data and real time data is fed at an appropriate time to a broadcast headend multiplexer 4 via a data feed 5. The CCS also generates electronic programme guide (EPG) data which is fed to an EPG multiplexer 6 via EPG data feed 7. Each item of EPG data includes a programme identifier (PID) and a system information (SI) table containing EPG information relating to that PID (eg. name, scheduled start time, splash screen data etc).

[0013] Broadcast TV stations 8 (BBC1) and 9 (Channel 4) each generate digital audio and video signals which are fed to the broadcast headend multiplexer 4 via respective data feeds 10,11. The data feeds 5,10,11 may be via dedicated cables or via broadcast on the air or any other suitable medium.

[0014] The broadcast TV stations 8,9 also generate EPG data which is fed to the EPG multiplexer 6 via respective data feeds 12,13. The EPG data may contain the programme name, broadcast TV station name and any other programme related information.

[0015] The broadcast headend multiplexer 4 multiplexes the digital data from the data feeds 5,10,11 and outputs the data serially to a transmitter 14 as an MPEG-II transport stream 30.

[0016] Similarly the EPG multiplexer 6 multiplexes the digital data from the EPG data feeds 7,12,13 and outputs the data serially to a transmitter 16 as an MPEG-II transport stream 31.

[0017] The transmitters 14,16 then transmit the data over a transmission medium 15. This may be a digital or analog television broadcast system, terrestrial or satellite, or cable, or the Internet, or the like.

[0018] A number of user interfaces (UIs) 17,18,19 etc. receive data from the transmission medium 15. The UIs can also send data to the CCS 2 via the public-switched-telephone-network (PSTN) 20 or other return path means (not shown) such as a cable-modem, or even via the transmission medium 15.

[0019] One of the user interfaces 17 is shown in detail in Figure 2. The UI comprises a conventional television set 21, a set-top box 22 and one or more input devices 33. The television set 21 comprises a cathode ray tube (CRT) 35 and a tuner 23 coupled to an aerial 24. The tuner 23 is selectively tuned by a central processing unit (CPU) 25 to receive data from the transmission medium 15. Data is passed to a demultiplexer 26 which demultiplexes the MPEG-II transport stream. Setup data and real time data is fed to the CPU 25 and video/audio data is fed to a display interface 28.

[0020] The CPU 25 accesses a random access memory (RAM) 27 and a read only memory (ROM) 32 to compile a display signal which is passed to the display interface 28 and merged with the audio/video signal from the demultiplexer 26. An input device 33 provides input to the CPU 25 from a user. An STB clock 41 feeds an STB clock signal to the CPU 25. Return path data is returned to the CCS 2 by the CPU 25 via a modem 34 and the PSTN 20.

[0021] An example of an interactive quiz game application will now be described.

[0022] Ten minutes before the scheduled start time of the quiz game, the CCS 2 downloads setup data relating to the application from the application data store 3, and feeds it to the broadcast headend multiplexer 4. The multiplexer 4 then places the data on a broadcast carousel whereby it repeatedly transmits the setup data on the transport stream 30 as described in more detail in EP-A-0998145.

[0023] The user interfaces can then download the setup data by switching the tuner 23 to receive data from the transport stream 30. Setup data with the required PID is downloaded by CPU 25 and saved in the RAM 27. Once all of the setup data has been downloaded (or sufficient components of it to allow execution to commence) timed execution of the scheduled interactive application can commence.

[0024] At the scheduled start time, the CCS 2 generates real time question data which is broadcast to the user interfaces. At the same time the CPU 25 automatically enters a game mode in which the user is presented with a series of questions based on the received question data. The user provides answers by selecting answer icons using the input device 33. At a set time following display of a question, the user is "locked out" (i.e. is prevented from entering an answer to the question) by the CPU 25 and the answer is displayed on the CRT 35. If the CPU 25 determines that the user has answered correctly, then a score is awarded and stored locally.

[0025] The questions and answers may fill the entire CRT screen. Alternatively the questions and answers may be overlaid on a real-time television broadcast of a presenter reading out the questions to competitors in a television studio, for example originating from the Channel 4 broadcast TV station 9.

[0026] At the end of the game, the CPU 25 transmits the user's score to the CCS 2 via the modem 34 and PSTN 20.

[0027] Each user has an account with a number of cash credits which are stored and managed by the CCS 2. On receipt of scores from a number of user interfaces the CCS 2 compares the scores and issues prizes to the users with the highest scores by adding cash credits to their accounts. This use of credits or tokens is described in more detail

EP 1 050 328 B1

in EP-A-0858225.

[0028] The way in which the system of Figures 1 and 2 handles time will now be described. The CCS clock 40 constantly generates a central clock signal CCS CLOCK. The STB clock 41 constantly generates a local clock signal STB CLOCK. In general STB CLOCK will be offset from CCS CLOCK and from the STB CLOCK signals of the other user interfaces 18,19 etc. In order to account for this lack of clock synchronisation, the CCS clock is periodically transmitted by the CCS 2 to the user interfaces 17-19 etc. Each CPU 25 can then calculate an offset value which is stored in a RAM 42:

$$\text{OFFSET} = \text{CCS CLOCK} - \text{STB CLOCK}.$$

[0029] This enables the CPU 25 to calculate CCS CLOCK at any time as:

$$\text{CCS CLOCK} = \text{STB CLOCK} + \text{OFFSET}.$$

[0030] Before, at or even after the start of the quiz game, the CCS 2 transmits a game start clock signal CCS CLOCK (game start) to the user interfaces defining the time according to the CCS at which the game starts. The CPU 25 in each STB can then calculate the STB game start time as:

$$\text{STB CLOCK (game start)} = \text{CCS CLOCK (game start)} - \text{OFFSET}.$$

[0031] During the quiz game, the CCS 2 retrieves question and answer data from the store 3 and places the data on the transport stream 30 before it is to be displayed by the user interfaces. Each item of data contains question/answer data, and also a relative game time (i.e. a time from the start of the game) at which the data is to be displayed. For instance the following sequence of data may be broadcast during a quiz game:

Data	Relative Game Time
Question A	60 seconds - 70 seconds
Answer A	70 seconds - 75 seconds
Question B	75 seconds - 85 seconds
Answer B	85 seconds - 90 seconds

[0032] Thus Question A is placed on the transport stream prior to 60 seconds from game start, and is displayed from 60-70 seconds from game start. During that 10 second period the user inputs his answer. At 70 seconds the user interface is locked out and the answer to question A is displayed for the next 5 seconds.

[0033] The CPU 25 handles the relative game time messages in the following way. The data and relative game time is input to the CPU 25. The CPU 25 then calculates the STB CLOCK time corresponding with the relative game time as:

$$\text{STB CLOCK (relative)} = \text{STB CLOCK (game start)} + \text{relative}$$

game time.

[0034] Thus the CPU displays Answer A between STB CLOCK (70 seconds) and STB CLOCK (75 seconds).

[0035] A fraudulent user can take advantage of this system as follows. This fraudulent user inserts an adjustment module 46 (shown in dotted lines in Figure 2) to adjust the signal STB CLOCK from the STB clock 41. This could either set STB CLOCK forward or backward by a fixed amount, or could slow down or speed up the rate of STB CLOCK. The adjustment module 46 is enabled by the user after STB CLOCK (game start) has been calculated. As a result the display of any subsequent question or answer data is delayed or advanced when compared to other STBs. By running two user interfaces (one with STB CLOCK adjusted, the other not) the fraudulent user can view the answers on one user interface and enter the correct answers on another user interface before it becomes locked out by the CPU 25 since that CPU 25 will not have reached the relative game time at which lock out occurs.

[0036] This fraudulent clock adjustment is detected in one or more of a number of ways as discussed below.

1. Return Path Request

[0037] At some point after the game start (either during or after the game) the CCS 2 sends a return path request to the user interfaces, asking them to send an acknowledgment back to the CCS 2 at a certain relative game time. If the acknowledgment from one of the user interfaces is delayed or advanced (when compared to the return time of acknowledgements from the other user interfaces) by more than a predetermined threshold then it is likely that STB CLOCK on that user interface has been adjusted. Therefore that user interface is identified and no prize is issued to the fraudulent user registered with the identified user interface.

2. Return Path Scores

[0038] The user interfaces are requested to send their scores back to the CCS 2 at the end of the quiz game. If the return time of the score from one of the user interfaces is delayed or advanced (when compared to the return time of scores from the other user interfaces) by more than a predetermined threshold, then that user interface is identified as a fraudulent interface, and no prize is issued to the user registered with the fraudulent interface.

[0039] Optionally, the following method may also be employed.

3. STB CLOCK monitor

[0040] A monitor 50 is provided to monitor STB CLOCK and OFFSET. This could be a separate module or part of the CPU 25. If either of these signals is adjusted then the monitor 50 sends a detection signal to the CPU 25 which informs the CCS 2 with an identification message. Thus if the user either adjusts STB CLOCK immediately after STB (game start) has been calculated; or resets STB CLOCK at the end of the game to attempt to disguise their fraud, then this adjustment will be detected by the monitor 50.

Claims

1. An interactive broadcast system comprising a plurality of user interfaces each comprising a local clock signal generator, wherein each user interface delivers interactive applications to a respective user with reference to its respective local clock signal; and a central control system (CCS) for broadcasting data to the user interfaces and for receiving data sent at a specific local time from the user interfaces, the CCS being adapted to identify fraudulent users by comparing the time at which said data are returned from a plurality of the user interfaces.
2. A system according to claim 1, wherein each user interface comprises a monitor for detecting adjustment of the local clock signal.
3. A system according to claim 1 or claim 2, wherein the CCS is adapted to send a return path request to the user interfaces and to monitor the time of receipt of corresponding return path data generated by the user interfaces in response to the return path receipt to identify user interfaces which have sent return path data which is advanced or delayed by more than a predetermined threshold.
4. A system according to claim 3, wherein the return path request causes the user interfaces to return a local score at the end of an interactive application as determined by the user interface.
5. A system according to any of the preceding claims, wherein the CCS is adapted to broadcast an application start signal to the user interfaces, wherein each user interface comprises means for calculating an application time local clock signal with reference to the application start signal, and wherein each user interface delivers interactive applications to a respective user with reference to its respective application time local clock signal.
6. A system according to any of the preceding claims, further comprising means for periodically broadcasting a central clock signal to the user interfaces; and wherein each user interface comprises means for calculating an offset signal with reference to the central clock signal and its respective local clock signal so as to enable the central clock signal to be obtained from the local clock signal.
7. A method of detecting fraudulent users in an interactive broadcast system, the method comprising

- (1) broadcasting data to a plurality of user interfaces from a central control system (CCS);

- (2) generating a local clock signal at each user interface;
- (3) delivering an interactive application to a respective user from each user interface with reference to its respective local clock signal;
- (4) receiving at the CCS data sent from the local interfaces at a specific local time; and,
- (5) identifying fraudulent users by comparing the time at which said data are returned from a plurality of the local interfaces.

8. A method according to claim 7, wherein step (4) comprises first sending a return path request to the user interfaces, step (5) comprising monitoring the time of receipt of return path data generated by the user interfaces in response to the return path request to identify user interfaces which have sent return path data which is advanced or delayed by more than a predetermined threshold.

9. A method according to claim 8 wherein the return path request causes the user interfaces to return a local score at the end of an interactive application as determined by the user interface.

10. A method according to any of claims 7 to 9, further comprising

- (6) broadcasting an application start signal to the user interfaces; and
- (7) calculating an application time local clock signal with reference to the application start signal,

wherein each user interface delivers interactive applications to a respective user with reference to its respective application time local clock signal.

11. A method according to any of claims 7 to 10, further comprising

- (8) periodically broadcasting a central clock signal to the user interfaces; and
- (9) calculating an offset signal with reference to the central clock signal and a respective local clock signal so as to enable the central clock signal to be obtained from the local clock signal.

Patentansprüche

1. Ein interaktives Sendesystem, umfassend eine Mehrzahl Benutzerschnittstellen, die jeweils einen lokalen Taktsignalerzeuger umfassen, wobei jede Benutzerschnittstelle mit Bezug auf ihr jeweiliges lokales Taktsignal interaktive Anwendungen an einen entsprechenden Benutzer liefert; und ein zentrales Steuersystem (CCS) zum Senden von Daten an die Benutzerschnittstellen und zum Empfangen von Daten, die zu einer bestimmten lokalen Zeit geschickt werden, von den Benutzerschnittstellen, wobei das CCS angepaßt ist, um betrügerische Benutzer zu identifizieren, indem die Zeit, zu der die Daten von einer Mehrzahl der Benutzerschnittstellen zurückgesandt werden, verglichen wird.
2. Ein System gemäß Anspruch 1, wobei jede Benutzerschnittstelle ein Überwachungssystem zum Erkennen der Einstellung des lokalen Taktsignals umfaßt.
3. Ein System gemäß Anspruch 1 oder Anspruch 2, wobei das CCS angepaßt ist, um eine Rücksendeweganforderung an die Benutzerschnittstellen zu schicken und die Empfangszeit der entsprechenden Rücksendewegdaten zu überwachen, die von den Benutzerschnittstellen als Reaktion auf die Rücksendeweganforderung erzeugt werden, um Benutzerschnittstellen zu identifizieren, die Rücksendewegdaten geschickt haben, die um mehr als einen vorbestimmten Schwellenwert voraus oder verspätet sind.
4. Ein System gemäß Anspruch 3, wobei die Rücksendeweganforderung bewirkt, daß die Benutzerschnittstellen am Ende einer interaktiven Anwendung einen durch die Benutzerschnittstelle bestimmten lokalen Punktestand zurücksenden.
5. Ein System gemäß einem der vorhergehenden Ansprüche, wobei das CCS angepaßt ist, um ein Anwendungsstartsignal an die Benutzerschnittstellen zu senden, wobei jede Benutzerschnittstelle Mittel zum Berechnen eines lokalen Anwendungszeittaktsignals mit Bezug auf das Anwendungsstartsignal umfaßt, und wobei jede Benutzerschnittstelle mit Bezug auf ihr jeweiliges lokales Anwendungszeittaktsignal interaktive Anwendungen an einen jeweiligen Benutzer liefert.

EP 1 050 328 B1

6. Ein System gemäß einem der vorhergehenden Ansprüche, weiterhin umfassend Mittel zum periodischen Senden eines zentralen Taktsignals an die Benutzerschnittstellen; und wobei jede Benutzerschnittstelle Mittel zum Berechnen eines mit Bezug auf das zentrale Taktsignal und ihr jeweiliges lokales Taktsignal versetzten Signals umfaßt, um zu ermöglichen, daß das zentrale Taktsignal aus dem lokalen Taktsignal erhalten wird.

7. Ein Verfahren zum Erkennen betrügerischer Benutzer in einem interaktiven Sendesystem, wobei das Verfahren umfaßt

- (1) Senden von Daten an eine Mehrzahl Benutzerschnittstellen von einem zentralen Steuersystem (CCS);
- (2) Erzeugen eines lokalen Taktsignals an jeder Benutzerschnittstelle;
- (3) Liefern einer interaktiven Anwendung von jeder Benutzerschnittstelle an einen jeweiligen Benutzer mit Bezug auf ihr jeweiliges lokales Taktsignal;
- (4) Empfangen von Daten, die zu einer bestimmten lokalen Zeit von den lokalen Schnittstellen geschickt werden, am CCS; und
- (5) Identifizieren betrügerischer Benutzer durch Vergleichen der Zeit, zu der die Daten von einer Mehrzahl der lokalen Schnittstellen zurückgesandt werden.

8. Ein Verfahren gemäß Anspruch 7, wobei Schritt (4) zuerst das Senden einer Rücksendeweg Anforderung an die Benutzerschnittstellen umfaßt,

wobei Schritt (5) das Überwachen der Empfangszeit der Rücksendewegdaten umfaßt, die von den Benutzerschnittstellen als Reaktion auf die Rücksendeweg Anforderung erzeugt werden, um Benutzerschnittstellen zu identifizieren, die Rücksendewegdaten geschickt haben, die um mehr als einen vorbestimmten Schwellenwert voraus oder verspätet sind.

9. Ein Verfahren gemäß Anspruch 8, wobei die Rücksendeweg Anforderung bewirkt, daß die Benutzerschnittstellen am Ende einer interaktiven Anwendung einen von der Benutzerschnittstelle bestimmten lokalen Punktestand zurücksenden.

10. Ein Verfahren gemäß einem der Ansprüche 7 bis 9, weiterhin umfassend

- (6) Senden eines Anwendungsstartsignals an die Benutzerschnittstellen; und
- (7) Berechnen eines lokalen Anwendungszeittaktsignals mit Bezug auf das Anwendungsstartsignal,

wobei jede Benutzerschnittstelle mit Bezug auf ihr jeweiliges lokales Anwendungszeittaktsignal interaktive Anwendungen an einen jeweiligen Benutzer liefert.

11. Ein Verfahren gemäß einem der Ansprüche 7 bis 10, weiterhin umfassend

- (8) periodisches Senden eines zentralen Taktsignals an die Benutzerschnittstellen; und
- (9) Berechnen eines mit Bezug auf das zentrale Taktsignal und ein jeweiliges lokales Taktsignal versetzten Signals, um zu ermöglichen, daß das zentrale Taktsignal aus dem lokalen Taktsignal erhalten wird.

Revendications

1. Système interactif de diffusion comprenant une pluralité d'interfaces-utilisateurs comprenant chacune un générateur de signal d'horloge locale, dans lequel chaque interface-utilisateur transmet des applications interactives à un utilisateur respectif en fonction de son signal respectif d'horloge locale ; et un système central de commande (SCC) servant à la diffusion de données auprès des interfaces-utilisateurs et à la réception des données émises à un temps local spécifique depuis les interfaces-utilisateurs, le SCC étant adapté pour identifier les utilisateurs fraudeurs en comparant le temps auquel lesdites données ont été renvoyées depuis la pluralité d'interfaces-utilisateurs.
2. Système selon la revendication 1, dans lequel chaque interface-utilisateur comprend un dispositif de surveillance servant à détecter le réglage du signal d'horloge locale.
3. Système selon la revendication 1 ou la revendication 2, dans lequel le SCC est adapté pour envoyer une requête de trajet de retour aux interfaces-utilisateurs et pour contrôler le temps de réception des données de trajet de

retour correspondantes générées par les interfaces-utilisateurs en réponse à la réception du trajet de retour afin d'identifier les interfaces-utilisateurs qui ont émis des données de trajet de retour présentant une avance ou un retard de plus d'un seuil prédéterminé.

- 5 4. Système selon la revendication 3, dans lequel la requête de trajet de retour amène les interfaces-utilisateurs à renvoyer un score local à la fin d'une application interactive tel que déterminé par l'interface-utilisateur.
- 10 5. Système selon l'une quelconque des revendications précédentes, dans lequel le SCC est adapté pour diffuser un signal de début d'application auprès des interfaces-utilisateurs, dans lequel chaque interface-utilisateur comprend un moyen permettant de calculer un signal d'horloge locale du temps d'application relativement au signal de début de l'application, et dans lequel chaque interface-utilisateur transmet des applications interactives à un utilisateur respectif relativement à son signal respectif d'horloge locale du temps d'application.
- 15 6. Système selon l'une quelconque des revendications précédentes, comprenant en outre un moyen servant à diffuser périodiquement un signal d'horloge centrale aux interfaces-utilisateurs, et dans lequel chaque interface-utilisateur comprend un moyen permettant de calculer un signal de décalage en fonction du signal d'horloge centrale et de son signal respectif d'horloge locale de sorte à permettre l'obtention du signal d'horloge centrale à partir du signal d'horloge locale.
- 20 7. Procédé de détection des utilisateurs fraudeurs à l'intérieur d'un système interactif de diffusion, le procédé comprenant :
 - (1) la diffusion de données auprès d'une pluralité d'interfaces-utilisateurs depuis un système central de commande (SCC) ;
 - 25 (2) la génération d'un signal d'horloge locale au niveau de chaque interface-utilisateur ;
 - (3) la transmission d'une application interactive à un utilisateur respectif depuis chaque interface-utilisateur en fonction de son signal respectif d'horloge locale ;
 - (4) la réception au niveau du SCC de données émises depuis les interfaces locales à un temps local spécifique ;
 - 30 (5) l'identification des utilisateurs fraudeurs en comparant le temps auquel lesdites données ont été renvoyées depuis la pluralité des interfaces locales.
- 35 8. Procédé selon la revendication 7, dans lequel l'étape (4) comprend tout d'abord l'émission d'une requête de trajet de retour aux interfaces-utilisateurs, l'étape (5) comprenant le contrôle du temps de réception des données de trajet de retour générées par les interfaces-utilisateurs en réponse à la requête de trajet de retour afin d'identifier les interfaces-utilisateurs ayant émis des données de trajet de retour présentant une avance ou un retard de plus d'un seuil prédéterminé.
- 40 9. Procédé selon la revendication 8, dans lequel la requête de trajet de retour amène les interfaces-utilisateurs à renvoyer un score local à la fin d'une application interactive tel que déterminé par l'interface-utilisateur.
- 45 10. Procédé selon l'une quelconque des revendications 7 à 9, comprenant en outre
 - (6) la diffusion d'un signal de début d'application auprès des interfaces-utilisateurs ; et
 - (7) le calcul d'un signal d'horloge locale du temps d'application en fonction du signal de début d'applicationdans lequel chaque interface-utilisateur transmet des applications interactives à un utilisateur respectif en fonction de son signal respectif d'horloge locale du temps d'application.
- 50 11. Procédé selon l'une quelconque des revendications 7 à 10, comprenant en outre
 - (8) la diffusion périodique d'un signal d'horloge centrale auprès des interfaces-utilisateurs ; et
 - (9) le calcul d'un signal de décalage en fonction du signal d'horloge centrale et à son signal respectif d'horloge locale de sorte à permettre l'obtention du signal d'horloge centrale à partir du signal d'horloge locale.
- 55

Fig.1.



